

(b) This Notice shall be marked on any reproduction of these data, in whole or in part.

RECOMMENDED VENDOR:

MARTIN TOOL & SUPPLY
PH: 254-752-2730
SHELL DARINA
EP GREASE 2
BOX OF 10 - 14.1 OZ. CARTRIDGES

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE INCHES

TOLERANCE ON:

DECIMIALS .X ± .130

± 5°

.XX ± .030 .XXX ± .010

BREAK DUTER EDGES .005/.020
BREAK HOLE EDGES .005 MAX
MACHINE FINISH 125 PER MIL-STD-10
SYMBOLS PER MIL-STD-8
CONCENTRICITY .006 TIR
SLOT & HOLES TO BE WITHIN .005 OF TRUE
POSITION WHEN LOCATED ON COMMON CENTER LINE

PART NO.	USED ON	QTY.

	MATERIAL		HEAT TREAT	FINISH	
		GREASE	N/A	N/A	
60					PR6
0					
X 2					\ \
N6.9					
DW 6.					
					E S C
			PRODUCT: SHELL DA	ΛΟΙΝΙΛ	<u>R</u>
			ERODUCI: SILLE DA EP GREA		
		OPFRATING	TEMPERATURE: UP	TO 250°F (121°C).	
					ATE (
					PPRO
					7 70
					8
					H A D
					3
	•				
	Y. T. S. C.				
Mara	athonNorc	O TITLE		MarathonNorco STANDARD	

GREASE

N/A

WEIGHT:

N/A

Aerospace, Inc.

CODE IDENT NO.

08844

SCALE:

DWG. NO.

99X2001-09